

SOLO DOMING VINYL

SELF ADHESIVE VINYL FILMS FOR DOMING TECHNOLOGY

GOLD DOMING VINYL

TECHNICAL DATA SHEET

General information:

Series of self- adhesive vinyl films is specially designed for doming technology. Is suitable for cutting, printable with the common LFP technologies such as solvent, eco-solvent, UV and screen-printing.

Application:

Manufacture of customized signs, badges and emblems for the automotive and promotional gadget markets.

* Not recommended on apolar substrates (like PE and PP).

Face material:

Gloss gold metallized rigid vinyl

Thickness: 80 μ

Adhesive:

Type: Acrylic permanent

Service temp.: -40°C/+140°C

Shear: very high

Tack: 15 N/25mm

Final adhesion: 7 N/25mm

Liner:

Type: One side siliconised polyester

Weight: 140 g/m²

Shelf life:

24 months, applicable only to the material delivered by WMT Baltic which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C \pm 2°C and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.