

| | | | |
|-----------------|--|-------------------|---|
| Substrate | | DIN 60001 | 100 % Polyester |
| Weave | | DIN ISO 9354 | woven fabric |
| Weight approx. | | DIN EN ISO 2286-2 | 175 g/m ² |
| Fire retardancy | | DIN 4102 B1 | yes |
| Application | | | indoor |
| Width | | DIN EN ISO 2286-1 | max. 510 cm / 201 inch (see overview) |
| Print side | | | width < 3 m: print side outside width > 3 m: print side inside |
| Roll length | | | 30 - 50 ± 0,5 m |
| Type of ink | | | UV-curable inks*, latex inks |

Advantages

- available in large width
- fast crease recovery
- stretchable
- soft
- dirt-repellent
- trimming cold (no fraying)

Applications

- frontlit
- lightbox, backlit
- frame tensioning systems

* please consider the risk of curling because UV-curable inks will still be hardening after a while



All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020

