

PROFILINE



[SPECIALITIES] : SOLO Block

GENERAL INFORMATION

280µ polyester film with polypropylen lyster coated from one side with white matt surface. Blocking light feature allows to be used for display applications if it is necessary not to pass light through.

Perfect waterproof, high density and high resolution printing characteristics. High quality coating gives a significantly short drying time and brilliant true color reproduction.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Particularly suitable for displays, posters, signs etc.

TECHNICAL DATA

Carrier:	One side coated polyester with polypropylen
Thickness:	315 µ +/- 5 %
Optical density:	1,45
Application temperature:	+10 - +40 °C
Service temperature:	- 20 - +50 °C
Water resistance:	Waterproof
Material durability:	2 years (unprinted film)

RECOMMENDATIONS FOR LAMINATING

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

SHELF LIFE

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

STANDARD DIMENSIONS

914 mm x 50 m
1270 mm x 50 m
1520 mm x 50 m

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of SOLO Media, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. SOLO Media makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.

MEDIA for [eco] SOLVENT-BASED