# SOLOMEDI,

# [WALLART]: Wallart Papyrus

### **GENERAL INFORMATION**

Papyrus textured wallpaper with paper backing (90 gsm) and vinyl coating (210 gsm), designed for printing with all solvent, HP Latex and UV-curable inks.

Resistant to mechanical damage (scratches). Material gives a great opportunity to make a custom made wallpaper. Image can be transferred to the wall with glue for heavy wallpaper. Great for design and decoration work. Wallpapers can be washed! Wallpaper is fire safe material and can be used in areas with high fire safety requirements.

### **APPLICATIONS**

Great for wall design and decoration. Applied as standart wallpaper using glue for heavy wallpapers.

### **SHELF LIFE**

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

# **SAFETY DATA SHEET**

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

# **TECHNICAL DATA**

Carrier: Papere with PVC coating for digital printing

Weight: 300 gsm + /- 15 gsm

Paper: 90 gsm +/- 15 gsm PVC Coating: 210 gsm +/- 15 gsm

Thickness:  $400 \mu +/-5 \%$ 

Color: white

Operating temperature: + 15 - +30 °C

Operating humidity: 15 to 80% RH

Water Resistance: Water resistant with Eco-Solvent ink

Flame Resistance: Class A, B1

### STANDART DIMENSIONS

1300 mm x 50 m

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of SOLO Media, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. SOLO Media makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.