

UZLEX DS 340 TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

Double coated film tape with a differential adhesive system. One side is coated with a permanent adhesive and the other with a clean removable / peel able adhesive. Open side is coated with a high performance permanent acrylic adhesive, giving good shear and peel performance. Closed side is coated with a special clean removable acrylic adhesive that leaves no adhesive residue on most substrates. Carrier is a 12 micron clear filmic polyester. Paper liner is a 80gsm havana brown glassine paper with a differential silicone treatment.

APPLICATIONS

Uzlex DS 340 is ideal for advertising, point of sale applications and works well with paper and glass substrates. It can be used in print artwork and lay-out applications. Can be used as core started and a closure tape.

TECHNICAL DATA	
Adhesive type:	Acrylic
Adhesion [N/25mm]:	10,00/ 3,75 +/-10 %
Carrier:	Polyester
Liner:	Havana brown glassine paper
Thickness [mm]:	0,12 +/- 5%
Temperature resistance [°C]:	-20 / +120

STANDART DIMENTIONS

25mm x 50m 50mm x 50m

SELF LIFE

When stored in the original packaging at 21°C and at 50% relatieve humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.