



UZLEX DS 343

TECHNICAL DATA SHEET

UZLEX
WWW.UZLEX.EU

PRODUCT DESCRIPTION

Double-sided Polyester adhesive tape coated with an acrylic adhesive of a high tack level. Beside an excellent ageing, weather and UV-resistance UZLEX DS 343 offers a well specific adhesion for mounting of unpolar plastic such as Polyethylene, Polypropylene and EPDM-rubber. UZLEX DS 343 is suitable for a long term mounting for a huge variety of materials such as metal, plastics, wood, paper, glass or ceramics, for in- and outdoor use.

APPLICATIONS

- Mounting of plastic profiles and for furniture.
- Self-adhesive equipment for rubber and EPDM-profiles.
- Mounting screens, holders and cable trunkings.
- Mounting of ABS parts in the automotive industry, etc.

TECHNICAL DATA

Adhesive type:	Solvent Acrylic, Transparent
Adhesion [N/25mm]:	18,00 +/- 10 %
Carrier:	PE, Clear
Liner:	Red mopp
Thickness [mm]:	0,205 +/- 5%
Temperature resistance [°C]:	-40 / +120

STANDART DIMENTIONS

6mm x 50m	15mm x 50m
9mm x 50m	19mm x 50m
12mm x 50m	

SELF LIFE

When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.