



UZLEX DS 328

TECHNICAL DATA SHEET

UZLEX
WWW.UZLEX.EU

PRODUCT DESCRIPTION

Double-sided tape based on a fleece coated with a solventacrylic adhesive with high initial tack. The adhesive has good ageing, UV and humidity resistance and has high specific adhesion on various materials such as plastic, metal, wood, glass, paper and several foams. The liner is not sensitive to humidity therefore retroactive creasing is eliminated. contact time. Suitable for die-cutting.

APPLICATIONS

- Splicing paper for manual or automatic roll change for the manufacturing of corrugated papers.
- Short term temperature resistance up to +200°C and therefore suitable for machinery with longer at the preheating cylinder.
- Mounting of polyester, polyether, PVC and polyethylene foams.
- Mounting of displays and promotional articles.
- Mounting of plates, cover-plates, holders and cable trunkings.

TECHNICAL DATA

Adhesive type:	Solvent acrylic
Adhesion [N/25mm]:	11,5 +/- 10 %
Carrier:	30my tissue paper
Liner:	White paper, double coated PE lamination treatment
Thickness [mm]:	0,12 +/- 0,01mm
Temperature resistance [°C]:	-40/ +120

STANDART DIMENTIONS

4mm x 50m	12mm x 50m
6mm x 50m	19mm x 50m
9mm x 50m	

SELF LIFE

When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.