

UZLEX DS 385TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

Double-sided adhesive polyethylene foam mounting tape, used for permanent bonding, mounting and fixing applications giving very good load bearing capability. UZLEX DS 385 is using acrylic pressure sensitive adhesive that has a good tack and adhesion properties. It has a good all-round performance and is ideal for moderate load bearing application for interior and exterior usage. High quality closed cell white polyethylene foam carrier. Cross linked foam has a good elongation and cohesive strength. UV and weather resistant.

APPLICATIONS

This tape is designed for in- and outdoor applications where high load bearing characteristics are required. Tape adheres well to a variety of substrates including wood, glass, metals and nonplasticized plastics. Typical applications are for example display hooks, cable clips, interior signs, name plates, decorative trims in extruded plastic/wood and electrical conduit.

High grade solvent acrylic adhesive offers a high initial tack which guarantees an easy mounting under industrial conditions. Mounting of displays, product samples, plates and screens.

| TE | LIN | Ш | CA | | n. | ۸Т | ٠, |
|-------|-----|---|----|-----|----|----------|----|
| - 1 - | пι | ч | LA | VI. | | - | H |

| Adhesive type: | Solvent acrylic, White | | |
|------------------------------|------------------------|--|--|
| Adhesion [N/25mm]: | 22,8 +/-10 % | | |
| Carrier: | Polyethylene foam | | |
| Liner: | White PE coated paper | | |
| Thickness [mm]: | 1,0 +/- 0,1mm | | |
| Temperature resistance [°C]: | +20/ +80 | | |

STANDART DIMENTIONS

6mm x 50m 19mm x 50m 9mm x 50m 12mm x 50m

SELF LIFE

When stored in the original packaging at 21°C and at 50% relatieve humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.