



PRODUCT DESCRIPTION

UZLEX PS 790 Grey Anti-Slip tape made from high quality self-adhesive synthetic rubber with abrasive surface. Rough material surface effectively prevent slipping, protecting people from falling even walking barefoot. Adhesive provides reliable fastening of tape to any smooth surface. Tape is water resistant.

APPLICATIONS

Main application areas: bathrooms and shower rooms, pools, spas, fitness centers, gyms, equipment for water sports, boats and yachts.

TECHNICAL DATA

Adhesive type:	Solvent Acrylic
Adhesion [N/25mm]:	13,73 +/-10 %
Bursting strength [kg/cm2]:	10
Color:	Grey
Carrier:	Synthetic rubber
Liner:	PE paper, 100gsm
Thickness [mm]:	0,8 +/- 0,2
Temperature resistance [°C]:	-30 / +60

STANDART DIMENTIONS

25mm x 18m 50mm x 18m

SELF LIFE

When stored in the original packaging at 21°C and at 50% relatieve humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.