

UZLEX SS Duo Grip black TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

UZLEX SS Duo Grip black works on the principle of interlocking mushroom heads, which provide a solid connection when pressed firmly together. It can be fastened as often as required either lenghtwise or crosswise and re-opened any time.

APPLICATIONS

Fastening solution that can replace screws, bolts and rivets.

This product is for use with many plastics (acrylic, polycarbonate and AS, powder coated paints and low surface energy materials (polypropylene and polyethylene).

TECHNICAL DATA	
Adhesive type:	Hot Melt, Transparent
Liner:	LDPE, transparent
Carrier:	polyamide, polyurethane coated, black
Thickness [mm]:	4,5 - without adhesive 5,4 - adhesive
Adhesion [N/cm2]:	35 +/- 5%
Temperature resistance [°C]:	-30 / +95

STANDART DIMENTIONS

25mm x 25m

SELF LIFE

When stored in the original packaging at 21°C and at 50% relatieve humidity the product has a shelf life of 6 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.