PROFILINE

[PAPERS] : SOLO Poster 150 (City Light)

GENERAL INFORMATION

150 gsm poster paper with white ssatin surface with good printability and handling characteristics. Good water and scratch resistance after complete drying. Printable with all solvent-, HP- latex- and UV-curable inks with high definition and brilliant print quality. Ideally sutable for backlight advertising panels, photo prints, posters, graphics, etc.

Can be used for indoor and short term outdoor applications.

RECOMMENDATIONS FOR LAMINATING

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

SHELF LIFE

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

TECHNICAL DATA

Carrier: paper with satin solvent ink coating

Thickness: $155 \,\mu + /-7 \,\%$

Weight: 150 gsm +/- 4 %

Color: white

Opacity: 99 % +/- 2

Application temperature: +10 - +40 °C

Service temperature: -30 - +50 °C

Type of ink: all solvent, eco-solvent, uv-curable and

HP Latex - inks

Protection: antystatic coating

Material durability: 1 year

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

STANDART DIMENSIONS

1370 mm x 50 m 1370 mm x 100 m 1600 mm x 50 m

1600 mm x 100 m

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of SOLO Media, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. SOLO Media makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.